

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1 1. (Currently Amended) An attachment device for connecting
2 a head and neck support device to a helmet, which
3 comprises:

4 (a) a base having a front surface with an
5 indention and a back surface with an opening extending
6 therebetween for positioning on the helmet with the back
7 surface of the base adjacent an outer surface of the helmet
8 and the opening of the base aligned with a hole in the
9 helmet;

10 (b) a button having an opening and positioned
11 ~~adjacent~~ in the indention of the front surface of the base
12 with the opening of the button aligned with the opening of
13 the base wherein when the button is depressed, the button
14 moves into the indention of the base;

15 (c) a resilient member positioned between the
16 front surface of the base and the button for biasing the
17 button in a direction away from the base;

18 (d) a post, having opposed first and second ends

19 with a head at the first end, for positioning through the
20 openings of the button and the base and the hole in the
21 helmet so that the second end of the post is adjacent an
22 inner surface of the helmet;

23 (e) a retainer for mounting on the second end of
24 the post adjacent the inner surface of the helmet for
25 securing the post in position in the hole in the helmet;
26 and

27 (f) a catch for connecting to the head and neck
28 support device and having an opening for connecting to the
29 head of the post by positioning the head of the post
30 through the opening.

1 2. (Currently Amended) The device of Claim 1 ~~wherein the~~
2 ~~front surface of the base has an indentation and wherein the~~
3 button has a front surface and a back surface and is
4 positioned in the indentation with the back surface adjacent
5 the base so that ~~in a fully retracted position, when the~~
6 button is depressed, the front surface of the button is
7 flush with the front surface of the base adjacent the
8 indentation.

1 3. (Original) The device of Claim 1 wherein the post has a
2 connector section adjacent the head and wherein the
3 connector section has a size less than the size of the
4 head.

1 4. (Original) The device of Claim 3 wherein the connector
2 section has a pair of opposed and parallel flat sections.

1 5. (Original) The device of Claim 4 wherein the head has a
2 pair of opposed and parallel flat sections adjacent and
3 parallel to the pair of flat sections of the connector
4 section.

1 6. (Original) The device of Claim 4 wherein the head has
2 an indicator line spaced between and parallel to the pair
3 of flat sections of the connector section.

1 7. (Currently Amended) The device of Claim ~~3~~ 4 wherein a
2 width of the connector section between the flat sections is
3 less than a width of the opening of the catch.

1 8. (Original) The device of Claim 1 wherein the opening of
2 the catch has a first section and a second section, wherein
3 a width of the first section is greater than a width of the
4 second section and greater than a width of the head of the
5 post and wherein the width of the second section is less
6 than the width of the head of the post.

1 9. (Original) The device of Claim 8 wherein the post has
2 a connector section adjacent the head, wherein a width of
3 the connector section is less than the width of the head of
4 the post and wherein the width of the connector section is
5 less than the width of the second section of the opening of
6 the catch so that the connector section is able to slide
7 into the second section of the opening of the catch.

1 10. (Original) The device of Claim 9 wherein the connector
2 section has a cylindrical shape so that when the connector
3 section is in the second section of the opening of the
4 catch, the catch can rotate around the connector section of
5 the post.

1 11. (Original) The device of Claim 8 wherein a channel
2 having parallel sides connects the first section of the
3 opening of the catch to the second section of the opening
4 of the catch, the channel having a width between the sides
5 less than a width of the first section and less than a
6 width of the second section, wherein the post has a
7 connector section adjacent the head, the connector section
8 having a pair of opposed and parallel flat sections, and
9 wherein the width of the channel is greater than a width of
10 the connector section between the flat sections so that the
11 connector section can be moved between the first and second
12 sections of the opening through the channel.

1 12. (Original) The device of Claim 11 wherein the
2 connector section has an essentially cylindrical shape with
3 curved sections spaced between the flat sections, wherein
4 a diameter of the connector sections between the curved
5 sections is greater than the width of the connector section
6 between the flat sections and the width of the channel
7 between the sides so that the flat sections of the
8 connector section must be parallel to and spaced between
9 the sides of the channel when the post is moved from the
10 first section to the second section of the opening through
11 the channel.

1 13. (Original) The device of Claim 8 wherein the catch has
2 a recess extending around a portion of a perimeter of the
3 second section of the opening, wherein a size of the recess
4 is greater than a size of the head of the post to allow the
5 head to extend into the recess when the post is in the
6 second section of the opening and the catch is connected to
7 the post.

1 14. (Original) The device of Claim 1 wherein the catch is
2 connected to the head and neck support device by a strap.

1 15. (Original) The device of Claim 1 wherein a size of the
2 back surface of the base adjacent the outer surface of the
3 helmet is greater than a size of the hole in the helmet.

1 16. (Original) The device of Claim 15 wherein a size of
2 the retainer adjacent the inner surface of the helmet is
3 essentially similar to the size of the back surface of the
4 base adjacent the outer surface of the helmet.

Claims 17-26 (Cancelled)

1 27. (New) An attachment device for connecting a head and
2 neck support device to a helmet, which comprises:

3 (a) a base, having a front surface and a back
4 surface with an opening extending therebetween, for
5 positioning on the helmet with the back surface of the base
6 adjacent to an outer surface of the helmet and the opening
7 of the base aligned with a hole in the helmet;

8 (b) a button having an opening and positioned
9 adjacent the front surface of the base with the opening of
10 the button aligned with the opening of the base;

11 (c) a resilient member positioned between the
12 front surface of the base and the button for biasing the
13 button in a direction away from the base;

14 (d) a post, having opposed first and second ends
15 with a head at the first end, for positioning through the
16 openings of the button and the base and the hole in the
17 helmet so that the second end of the post is adjacent an
18 inner surface of the helmet;

19 (e) a retainer for mounting on the second end of
20 the post adjacent the inner surface of the helmet for
21 securing the post in position in the hole in the helmet;
22 and

23 (f) a catch for connecting to the head and neck
24 support device and having an opening with a first section

25 and a second section for connecting to the head of the post
26 by positioning the head of the post through the opening
27 wherein a width of the first section is greater than a
28 width of the second section and greater than a width of the
29 head of the post, wherein the width of the second section
30 is less than the width of the head of the post, wherein the
31 catch has a recess extending around a portion of a
32 perimeter of the second section of the opening and wherein
33 a size of the recess is greater than a size of the head of
34 the post to allow the head to extend into the recess when
35 the post is in the second section of the opening and the
36 catch is connected to the post.